

# Specifications

## Specifications and performances @23°C ±5°C

### DC voltage: Measurement

Range	Measuring range	Resolution	Accuracy / 1yr
0 - 10 V	-2 / 12 V	1 mV	0.015% RDG + 2 mV
25 V	-2 / 25 V	1 mV	0.015% RDG + 2 mV
50 V	-5 / 50 V	1 mV	0.015% RDG + 4 mV

Temperature coefficient: < 15 ppm/°C beyond reference domain

Rin = 1 MΩ ± 1%

Common mode rejection: 120 dB at 50 and 60 Hz

### DC voltage: Emission

Range	Emission range	Resolution	Accuracy / 1yr
0 - 10 V	0 / 12 V	1 mV	0.015% RDG + 2 mV
15 V	0 / 15 V	1 mV	0.015% L + 2 mV

Temperature coefficient: < 15 ppm/°C beyond reference domain

Rising time: < 1 ms (0 V to 15 V accross 1 MΩ load)

Internal resistance: ≤ 1 Ω

VLF Noise: < 1 mVcc (at F < 100 Hz)

### DC current: Measurement

With or without loop supply

Range	Measuring range	Resolution	Accuracy / 1an
0-20 mA	-6 / 24 mA	1 μA	0.015% RDG + 2 μA
4-20 mA	3.2 / 24 mA	1 μA	0.015% RDG + 2 μA
25 mA	-6 / 25 mA	1 μA	0.015% RDG + 2 μA

Temperature coefficient: < 20 ppm/°C beyond reference domain

Loop power supply: 24 V ± 10%

HART® compatibility: R = 250 Ω ± 5%

Rin < 30 Ω

Common mode rejection: 120 dB at 50 and 60 Hz

### DC current: Emission

With or without loop supply

Range	Emission range	Resolution	Accuracy / 1yr
0-20 mA	500 μA / 24 mA	1 μA	0.015% RDG + 2 μA

4-20 mA	3.2 / 24 mA	1 $\mu$ A	0.015% RDG + 2 $\mu$ A
25 mA	500 $\mu$ A / 25 mA	1 $\mu$ A	0.015% RDG + 2 $\mu$ A

Temperature coefficient: < 20 ppm/°C beyond reference domain

Rising time: < 500  $\mu$ s (0 to 20 mA across 20  $\Omega$  load)

VLF Noise: < 1  $\mu$ A (at F < 100 Hz)

## Continuity test

Preset step emission and valve test

Configuration of steps or increments with adjustable frequency

Linearity tests over linear or quadratic signals

	0%	25%	50%	75%	100%	
4-20 mA linear		4	8	12	16	20
0-20 mA linear		0	5	10	15	20
4-20 mA quad		4	5	8	13	20
0-20 mA quad		0	1.25	5	11.25	20
4-20 mA valves	3.8-4-4.2			12		19, 20, 21

## Further features

Scaling in measurement and simulation modes	This function allows sensors to be corrected after a calibration. Scaling is performed using up to 10 segments, in order to fit with the real calibrated value.
HART compatibility	Equipped with a non-disturbing digital transmission resistance, it is possible to measure the current output of any transmitter using HART protocol.
Statistical functions	Continuous display of average, minimum and maximum value of the signal under monitoring, as well as number of measurements.
Simple and cyclical ramp generation	Ramps can be generated by setting low and high dwell, rising and falling times, stabilization and delay times (1 to 3,600 s). Delay time enables a single user to launch the ramp and go to the control panel.
Steps simulation	This mode allows predefined values to be sent with programmable amplitude and frequency.
Square root	In current measurement and simulation, this function allows taking into account a quadratic signal coming from transmitter of type $\Delta$ P.

## General specifications

Size	157 x 85 x 45 mm
Weight	306 g
Display	160 x 160 pixel liquid crystal graphical display

	with backlite Display of result as table of values or trend curve
Power supply	4 AA batteries 1.5 V or rechargeable Ni-Mh batteries with internal charger in option Autonomie : > 53 h en mesure tension et courant et simulation tension > 12 h en simulation courant
Communication ports	USB

### Environmental specifications

Reference range	23°C ± 5°C (RH: 45 to 75 % w/o condensing)
Operating reference range	-10 to 50°C (RH: 20 to 80 % w/o condensing)
Limit operating range	-15°C to +55°C (RH: 10 to 80 % w/o condensing) (70% at 55°C)
Storage temperature limits	-30°C to +60°C
Maximum height	0 to 2,200 m
IP protection	IP54 according to EN60529

### Safety specifications

Protections	<ul style="list-style-type: none"> <li>• Electronic protection up to 250 V for 'voltage' wires</li> <li>• Fuse protection for 'current' wires</li> <li>• Protection against 'current' circuit breaking during inductive resistance measurements</li> </ul>
Class	In accordance with EN 61010-1 Category II, pollution 2
Rated voltage	60 V
Chocks and vibrations	EN 61010-1
EMC conformity	

# Models and accessories

## Instruments:

CP 6632                  Handheld process calibrator for voltage and current

Delivered in standard with:

- User manual
- 4 AA batteries
- 2 cables and crocodile clips
- Protection sheath
- Carrying strap
- Factory test report

## Accessories:

AC6908                  Soft carrying case for hand-held instruments

AN6011                  Charger + batteries for hand-held instruments

## Certification:

QMA11EN              COFRAC certificate of calibration

With all relevant data points where the device has been tested

## Packing information:

Size                      157 x 85 x 45 mm

Weight without packing 306 g