



Blue Gizmo Sound Level Meter - BG325

Features

- Mini Size
- Newly Design Shape
- Low Cost High Performance
- MAX/MIN Function
- Level Range Display
- AC Singal Output
- Resolution 0.1 dB
- IEC 651 Type II



SPECIFICATIONS

Microphone	Electric condenser microphone
Accuracy	± 1.5 dB (ref 94dB @1KHz)
Level Range	Low = 35 ~ 80 dB Medium = 50 ~ 100 dB High = 80 ~ 130 dB
Frequency Weighting	A , C
Time Weighting	Fast , Slow
Auxiliary Outputs	AC Signal Output
Dynamic Range	50 dB
Frequency Range	31.5Hz to 8KHz
Battery Type	9V Battery NEDA 1604, IEC 6F22, JIS 006P
Battery Life	50 hours (with alkaline battery)
Operation Temp.	0°C~ 40°C (<80% R.H.)
Storage Temp.	-10°C~ 60°C (<70% R.H.)
Dimension	232mm x 54mm x 34mm (9.1" x 2.1" x 1.3")
Weight	Approx. 200g
Accessories	Manual, 9V Battery, Calibration Screwdriver, Windscreen

MODEL

DESCRIPTION

BG 325	Blue Gizmo Sound Level Meter
--------	------------------------------